

# KU36

Ultra slim, high power  
sub woofer

**array**  
**K**

## DATASHEET



### Features:

- Unique performance-to-size ratio
- 6" long-excursion woofer
- Double 6" passive radiator
- Extended frequency response
- Electronically protected
- Integrated flying points
- Double voice coil (4Ω+4Ω)
- Top quality components for outstanding performance
- Weather proof, suitable for outdoor installations
- Available in black or white

### Applications:

- Theatre, Club, Churches
- To extend the low range in small and midium rooms
- Portable and installed AV systems
- Stage and AV studio monitoring

<b>KU36</b>	
<b>Acoustics</b>	
Power handling	2 X 80 W <sup>(AES)</sup>
Impedance	2 X 4Ω
Operating frequency range	45 Hz - 300 Hz
SPL 1W / 1mt	89 dB
Maximum SPL	115 dB continuous - 121 dB peak
<b>Transducers</b>	
Full range	1 X 6" Neodymium magnet with 1.5" voice coil + 2 X 6" passive transducer
<b>Audio Input</b>	
Connectors	4-pin Phoenix
Wiring	Pin1=Ch 1+, Pin2=Ch 1-, Pin3=Ch 2+, Pin4=Ch 2-
<b>Recommended Amplifiers</b>	
KA1-1, KA7-7, KA10-10	
<b>Physical</b>	
Dimensions	50.7 x 17.5 x 10.6 cm (19.96" x 6.89" x 4.17")
Weight	6.4 Kg (14.11 lbs)
New materials and design are introduced into existing products without previous notice. Present systems may differ in some respects from those presented in this brochure.	

[www.k-array.com](http://www.k-array.com)

HP Sound Equipment s.r.l. Viale Roma 7/i - 50037 - San Piero a Sieve (FI), Italy  
tel. +39 055 8487222 - fax. +39 055 8487238 - e-mail: [info@k-array.com](mailto:info@k-array.com)